

Specifications

Keystone Adapter Plate

KEY FEATURES

- Designed to be a customizable plate to mix copper & fiber
- Applicable for all Signamax keystone footprint connectors
- Compatible with Signamax LGX footprint wall & rack-mount optical fiber enclosures & panels
- Compatible with Signamax high-density keystone modules
- Plunger locks ("push-pins") offers toolless installation & removal



ORDERING INFORMATION

PART NO.	DESCRIPTION
UFE-B-K6-B	6-Port Keystone Module Adapter Plate, No Modules

Adapter plates are available pre populated with keystone modules, contact customer service.



SPECIFICATIONS

CONSTRUCTION

Plate: 16-gauge steel with corrosive resistant black finish **Plunger Locks:** Polycarbonate/Nylon/Polyester

Footprint: LGX
DIMENSIONS

0.40" D x 5.12" W x 1.18" H (10 mm x 130 mm x 30 mm)

Plunger Lock Spacing, CTC: 4.65" H (118 mm)

Mounting Opening (Min): 4.17" W x 1.06" H (106 mm x 27 mm)

CAPACITY

Six high-density keystone modules

WARRANTY

5 - Year Limited Component



^{*} LGX Modular Optical Fiber Panel (RMF3-B) with Panel-Mount Cable Management Bar (CMB-550-M). All pieces sold separately.



